



Quality is in our nature

Passenger car engine oils - Fully Synthetic

## Eurol Super Lite 5W-30

Fully synthetic oil for gasoline and diesel engines, with or without turbo

### Description

Eurol Super Lite 5W-30 is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil can be applied for cars equipped with catalytic converters, turbo charged engines and for direct fuel injection systems.

Eurol Super Lite 5W-30 provides an extremely quick and stable lubricant film at the cold start and offers high thermal stability under heavy duty operating conditions.

Eurol Super Lite 5W-30 not only offers extremely good wear protection, but also protects against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits.

Eurol Super Lite 5W-30 offers fuel saving properties and can be mixed with both synthetic and mineral motor oils.

Eurol Super Lite 5W-30 is also recommended for the BMW engines requiring the BMW Longlife-01<2019 performance.

### Specifications

Approved

**API SL**

Recommended for use

API SN/CF

ACEA A3/B4

VW 502.00

MB 229.3

Renault RN0710

Renault RN0700

VW 505.00

### Physical properties

|                               |               |             |
|-------------------------------|---------------|-------------|
| Colour                        | brown         |             |
| Density at 20°C               | 0.848 kg/l    | ASTM D 1298 |
| Viscosity, kinematic at 40°C  | 66.2 cSt      | ASTM D 445  |
| Viscosity, kinematic at 100°C | 11.2 cSt      | ASTM D 445  |
| Viscosity Index               | 169           | ASTM D 2270 |
| Viscosity, dynamic (CCS)      | 4529 cP       | ASTM D 2602 |
| Base number                   | 10.4 mg KOH/g | ASTM D 2896 |
| Sulphated ash                 | 1.31 wt%      | ASTM D 874  |
| Flash point                   | 213 °C        | ASTM D 93   |
| Pour point                    | -45 °C        | ASTM D 97   |

E100091

Version 3.0, 21-07-2021

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com