



Quality is in our nature

Passenger car engine oils - Fully Synthetic

# Eurol Evolence 5W-20

## Fully synthetic long-life motor oil

### Description:

Eurol Evolence 5W-20 is a fully synthetic engine oil, especially suitable for American and Asian petrol engines in passenger cars, SUV's, delivery vans and hybrids. This engine oil can be used in cars equipped with catalytic converters, turbo charged engines and direct injection systems where API SP(-RC) or ILSAC GF-6a is prescribed. Eurol Evolence 5W-20 is compatible with petrol fuels containing up to 85% ethanol (E85) as well as LPG and CNG.

Eurol Evolence 5W-20 provides optimum lubrication and cleaning for in particular Asian and American petrol engines from different automobile manufacturers as Ford, Chrysler, GM, Toyota, Lexus, Kia, Subaru, Mitsubishi and Honda.

This oil offers ultimate protection for hybrids and engines running under start-stop conditions. Its exceptionally low viscosity allows it to be used the year round, also during very low temperatures in the wintertime.

Eurol Evolence 5W-20 is designed to give improved fuel economy, turbocharger protection, and emission control system compatibility. This oil offers excellent protection against wear, corrosion, sludge and deposits as soon as the engine has started up to ensure maximum engine durability.

Eurol Evolence 5W-20 minimizes the risk of LSPI (Low Speed Pre Ignition) in modern engines with GDI/and TGDI and gives ultimate protection to the timing chain against deposits and wear.

Eurol Evolence 5W-20 is backward compatible to previous API specifications as API SM, SN and SN Plus as well as ILSAC GF 4 and GF-5.

### Specifications

Approved Chrysler MS 6395

**API SP** GM 6048-M

Performance level

API SP-RC

ILSAC GF-6A

GM dexos 1 Gen 2

Recommended for use

API CF

Ford WSS-M2C945-A

Ford WSS-M2C930-A

Fiat 9.55535-CR1

### Physical properties

Colour	amber	
Density at 20°C	0.846 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	47.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	8.7 cSt	ASTM D 445
Viscosity Index	163	ASTM D 2270
Viscosity, dynamic (CCS)	3431 cP	ASTM D 2602
Base number	8.5 mg KOH/g	ASTM D 2896
Sulphated ash	0.85 wt%	ASTM D 874
Flash point	209 °C	ASTM D 93
Pour point	-39 °C	ASTM D 97

E100130

Version 5.0, 24-12-2021

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com