



Quality is in our nature

Passenger car engine oils - Fully Synthetic

Eurol Fluence DXS 5W-30

Fully synthetic long-life motor oil based on mid SAPS technology

Description:

Eurol Fluence DXS 5W-30 is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil can be used in cars equipped with catalytic converters, turbo charged engines, soot filters and direct injection systems.

good wear protection but also protects against rust and oxidation, while special additives keep the engine clean from dirt, sludge and deposits during the sometimes extremely long drain intervals.

Eurol Fluence DXS 5W-30 offers an extremely high protection over prolonged drain intervals. Especially recommended for Euro-4, -5 and -6 cars of Opel and Mercedes Benz with soot filters to prevent filter blocking. Because of this, Eurol Fluence DXS 5W-30 has low sulphated ash contents and also low levels of phosphor and sulphur (so called "mid SAPS" technology).

Eurol Fluence DXS 5W-30 is also suitable for all Volkswagen Seat, Audi and Skoda cars with normal drain intervals. Furthermore, this oil is an excellent choice for most Mercedes passenger cars and light duty commercial vehicles with or without a soot filter.

Eurol Fluence DXS 5W-30 not only offers an extremely

Specifications

<u>Approved</u>	MB 229.31
API SN	GM dexos 2
MB-Approval 229.52	<u>Recommended for use</u>
MB-Approval 229.51	VW 505.00
BMW Longlife-04	GM-LL-A-025
OV0401547	GM-LL-B-025
<u>Performance level</u>	Fiat 9.55535-S3
API CF	Dexos D
ACEA C3	
VW 502.00	
VW 505.01	

Physical properties

Colour	brown	
Density at 20°C	0.85 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	71 cSt	ASTM D 445
Viscosity, kinematic at 100°C	12 cSt	ASTM D 445
Viscosity Index	170	ASTM D 2270
Viscosity, dynamic (CCS) at -30 °C	5590 cP	ASTM D 2602
MRV	22000 cP	ASTM D 4684
HTHS	3.5 cP	CEC CL 23
Base number	7.4 mg KOH/g	ASTM D 2896
Sulphated ash	0.78 wt%	ASTM D 874
Flash point	200 °C	ASTM D 93
Pour point	-39 °C	ASTM D 97

E100076

Version 7.1, 07-06-2021

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com