



Quality is in our nature

Additives - Fuel

# Eurol Diesel Flow Improver

Fuel additive to lower the cold flow point of diesel fuel

## Description

Eurol Diesel Flow Improver is an additive developed to enhance cold flow properties of diesel for cold climates in order to avoid diesel flow problems during winter conditions. When the fuel temperature reaches the cloud point, the paraffin which is present in diesel fuel begins to form wax crystals. These crystals flow with the fuel and coat the filter element, as a consequence this quickly reduces the fuel flow, starving the engine.

Eurol Diesel Flow Improver is an excellent cold flow improver by modifying wax crystal formation at low temperatures for both high and low sulfur diesel fuels. High sulfur diesel fuel has different cold flow characteristics than its successor, low sulfur diesel. A diesel fuel that is not tailored to low temperatures will require the addition of Eurol Diesel Flow Improver to keep the engine from fuel starvation.

Eurol Diesel Flow Improver significantly lowers the temperature at which waxes clump together, which keeps the fuel flowing through the filter. This will allow

you to keep driving in winter.

Eurol Diesel Flow Improver is formulated to dissolve when it is mixed with diesel fuel, as long as it is added to the diesel fuel before the fuel reaches its cloud point.

A 250ml bottle of Eurol Diesel Flow Improver is recommended for use in 35L to 65L of fuel. Most fuel producers add a small quantity of these kind of chemicals in the required quantities to the diesel fuel they sell to achieve the necessary protection during the colder months.

The amount of cold flow improvers added by the fuel company, however, has been tailored to the country in which the fuel will be sold. If you travel to a colder country with fuel from a warmer country, problems can be avoided by using Eurol Diesel Flow Improver.

Users should consult the Material Safety Data Sheet of Eurol Diesel Flow Improver for information about storage and shelf life. Please ask Eurol Research & Development if

## Physical properties

Colour	Colourless	
Density at 20°C	0.883 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	2.8 cSt	ASTM D 445
Flash point	65 °C	ASTM D 93

E802484

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com