



*Quality is in our nature*

Technical fluids - Aerosols

# Eurol PTFE Super Lube Spray 400ML

## Lubricant with PTFE

### Description

Eurol PTFE Spray is high quality lubricant based on PTFE and is proper for the lubrication of metal and plastic parts. The product nebulizes as a lubricant with penetration properties and solidifies at a later stage as a grease.

Eurol PTFE Spray is specially developed for the lubrication of parts that are long-term exposed to high load. The PTFE offers a long-term protection against friction and prevents wear.

Eurol PTFE Spray can be used in many applications where contact between plastics/rubbers with metal needs to be lubricated. Applications such as machines, pulleys, chains, derailleurs, roller bearings and conveyors.

Eurol PTFE Spray must be shaken well before use. The to be treated object must be cleaned, degreased and dried before use. Spray at approx. 20-25 cm from the object. To achieve best results, Eurol PTFE Spray should be applied when the to be treated objects are in motion,

if possible.

Use Eurol PTFE Spray only in well ventilated areas. In case of eye contact immediately rinse eyes with plenty of water.

Eurol PTFE Spray has a shelf life of 3 years in an unopened container in a cool and dry place with a temperature range between +5°C and +25°C.

### Physical properties

---

Colour	colourless to slightly yellow
--------	-------------------------------

---

E701460

Version 1.1, 18-06-2019

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com