



Quality is in our nature

Passenger car engine oils - Fully Synthetic

Eurol Maxence RC 10W-60

Fully synthetic motor oil for race and rally applications

Description

Eurol Maxence RC 10W-60 is an ultra modern fully synthetic motor oil for diesel, gasoline and LPG engines in passenger cars and light duty commercial vehicles. The special additive package makes this oil suitable for race and rally applications as well.

Eurol Maxence RC 10W-60 provides a quick and stable lubricant film, protecting all moving parts against wear, even under the most heavy duty operating conditions. Because of the special additives, this oil has an excellent thermal and oxidation stability.

Eurol Maxence RC 10W-60 reduces combustion deposits, wear and enables a higher power-output. This oil offers an excellent corrosion protection, while deposits are reduced to a minimum and the viscosity stays in grade.

Specifications

Performance level

API SN/CF

ACEA A3/B4

Recommended for use

VW 500.00

MB 229.1

VW 505.00

Fiat 9.55535-H3

Physical properties

Colour	brown	
Density at 20°C	0.859 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	162.2 cSt	ASTM D 445
Viscosity, kinematic at 100°C	25.5 cSt	ASTM D 445
Viscosity Index	192	ASTM D 2270
Viscosity, dynamic (CCS)	3362 cP	ASTM D 2602
Base number	10.4 mg KOH/g	ASTM D 2896
Sulphated ash	1.31 wt%	ASTM D 874
Flash point	210 °C	ASTM D 93
Pour point	-42 °C	ASTM D 97

E100061

Version 2.1, 18-06-2021

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com