





Passenger car engine oils - Fully Synthetic

Eurol Fortence 5W-30

Fully synthetic fuel economy longlife engine oil for Ford and Jaguar

Description:

Eurol Fortence 5W-30 is a fully synthetic fuel economy engine oil for gasoline, LPG and diesel engines in most Ford passenger cars and light duty commercial vehicles from 2012, as well as some Jaguar models.

Eurol Fortence 5W-30 can also be used for all previous models for which Ford WSS-M2C-912A or 913A/B/C is prescribed.

Eurol Fortence 5W-30 establishes a highly stable lubricant film within a short amount of time at the cold start, which offers an extremely high oxidation stability and wear protection.

Eurol Fortence 5W-30 allows long drain intervals (up to 30.000 km) for the latest models of Ford and Jaguar.

Eurol Fortence 5W-30 offers extra fuel saving properties and the product can be mixed with both synthetic and mineral motor oils.

Specifications

Approved

Ford WSS-M2C913-D

Performance level

API SN/CF

API SL

ACEA A5/B5

STJLR 03.5003

Renault RN0700

Recommended for use

Fiat 9.55535-G1

Fiat 9.55535-N1

Physical properties

Colour	amber	
Density at 20°C	0.848 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	53.3 cSt	ASTM D 445
Viscosity, kinematic at 100°C	9.6 cSt	ASTM D 445
Viscosity Index	166	ASTM D 2270
Viscosity, dynamic (CCS)	3490 cP	ASTM D 2602
Base number	10.1 mg KOH/g	ASTM D 2896
Sulphated ash	1.22 wt%	ASTM D 874
Flash point	207 °C	ASTM D 93
Pour point	-48 °C	ASTM D 97

E100065 Version 4.1, 22-10-2020