



Quality is in our nature

Passenger car engine oils - Semi-synthetic

# Eurol Turbosyn 10W-40

Semi-synthetic motor oil, universal applicability

## Description

Eurol Turbosyn 10W-40 is a semi-synthetic motor oil with a universal applicability in gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil provides a good lubricant film at a cold start, also at low temperatures and offers an excellent lubricant film at high operating temperatures as well.

Eurol Turbosyn 10W-40, with a special additive package, enable the engine to perform under all conditions. Also fuel saving and exhaust emission reduction can be obtained with this product. Because of the unique formulation, the oil has a low evaporation tendency.

Eurol Turbosyn 10W-40 offers excellent anti-wear, anti-foam and corrosion protection properties. Together with deterging and dispersing capabilities, the oil keeps the engine clean and in a safe condition.

Because of the high temperature stability, Eurol Turbosyn 10W-40 will maintain its quality level and will not thicken.

## Specifications

### Performance level

API SL/CF  
ACEA A3/B4  
VW 501.01  
MB 229.1  
VW 505.00

### Recommended for use

VW 500.00  
Fiat 9.55535-G2

## Physical properties

Colour	brown	
Density at 20°C	0.861 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	100.4 cSt	ASTM D 445
Viscosity, kinematic at 100°C	15 cSt	ASTM D 445
Viscosity Index	157	ASTM D 2270
Viscosity, dynamic (CCS)	5411 cP	ASTM D 2602
Base number	10.4 mg KOH/g	ASTM D 2896
Sulphated ash	0.95 wt%	ASTM D 874
Flash point	210 °C	ASTM D 93
Pour point	-39 °C	ASTM D 97

E100094

Version 2.4, 18-06-2021

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com