



Quality is in our nature

Heavy duty diesel engine oils - low SAPS

# Eurol Geo-Max SA 10W-30

## Universal Heavy Duty Diesel engine oil

### Description:

Eurol Geo-Max SA 10W-30 is a premium mixed fleet engine oil for naturally aspirated and turbocharged four-stroke diesel and gasoline engines operating under severe service in a wide range of climatic conditions, delivering API CK-4 performance.

Eurol Geo-Max SA 10W-30 is formulated to address major North American and European OEM specifications needs for new engine hardware and operating conditions.

Eurol Geo-Max SA 10W-30 has excellent wear, deposit, sludge and corrosion protection. It improves oxidation protection performance by over 60% compared to the previous API CJ-4 technology.

Eurol Geo-Max SA 10W-30 is fully backwards compatible with API CJ-4, API CI-4+, CI-4 and previous.

Eurol Geo-Max SA 10W-30 delivers sustained emission control durability in particulate filters and it is compatible with advanced after treatment devices. It exceeds all current emission control systems as EGR (Exhaust Gas Recirculation), DPF (Diesel Particulate Filter) or SCR (Selective Catalytic Reduction).

Eurol Geo-Max SA 10W-30 is formulated for use in all vehicles with diesel fuels ranging in sulfur content up to 500 ppm. Eurol Geo-Max SA 10W-30 is also suitable in gasoline engines where SAE 10W-30 with API SN performance is specified.

### Specifications

<u>Approved</u>	Deutz DQC III-10 LA	Detroit Diesel DDC 93K218
<b>API CK-4</b>	MTU type 2.1	MAN M 3575
<b>Volvo VDS-4.5</b>	Cummins CES 20086	Mack EO-O PP
<b>Mack EOS-4.5</b>	Detroit Diesel DDC93K222	JASO DH-2
<b>Renault VI RLD-3</b>	Ford WSS-M2C171-F1	
<u>Performance level</u>	MAN 3775	
API CJ-4	<u>Recommended for use</u>	
ACEA E9	API SN/CF	
MB 228.31	ACEA E7	
Volvo VDS-4	MAN M 3275	
Caterpillar ECF-3	CES 20081	

### Physical properties

Colour	brown	
Density at 20°C	0.865 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	82 cSt	ASTM D 445
Viscosity, kinematic at 100°C	12 cSt	ASTM D 445
Viscosity Index	141	ASTM D 2270
Viscosity, dynamic (CCS)	5660 cP	ASTM D 2602
HTHS	3.5 cP	CEC CL 23
Base number	10.0 mg KOH/g	ASTM D 2896
Sulphated ash	0.99 wt%	ASTM D 874
Flash point	208 °C	ASTM D 93
Pour point	-37 °C	ASTM D 97

Available in 60L, 210L

E100168  
Version 6.0, 30-03-2021

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com