



Quality is in our nature

Motorcycle oils 4T - Fully Synthetic

Eurol Harley Twinlube-FS 20W50

Fully synthetic motor oil for 4-stroke motorcycles

Description

Eurol Harley Twinlube-FS 20W-50 is a fully synthetic engine oil without a friction modifier, especially developed for 4-stroke motorcycles.

Eurol Harley Twinlube-FS 20W-50 is based on fully synthetic base oils, giving optimized friction characteristics and offering excellent protection against wear, deposits, sludge and oxidation under all conditions. Aeration and foaming are avoided even under the roughest and toughest conditions.

Eurol Harley Twinlube-FS 20W-50 has a low volatility, reducing oil thickening and oil consumption to a bare minimum.

Due to the sophisticated formulation, this oil offers an excellent protection to gearboxes and wet disc clutches and prevents clutches from slipping and sticking.

Despite the high loads between the gears, the dedicated oil thickener hardly breaks down, so that even at high

temperatures, the viscosity stays in grade to assure a strong lubricant film.

At low temperatures, Eurol Harley Twinlube-FS 20W-50 quickly builds up a tenacious lubricant film for an optimum protection at the cold start.

Specifications

Performance level

API SJ

JASO MA

JASO MA2

Physical properties

Colour	Amber	
Density at 20°C	0.852 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	128.2 cSt	ASTM D 445
Viscosity, kinematic at 100°C	18.2 cSt	ASTM D 445
Viscosity Index	159	ASTM D 2270
Viscosity, dynamic (CCS)	2164 cP	ASTM D 2602
Flash point	210 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

E100376

Version 1.1, 07-12-2017

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com