



Quality is in our nature

Tractor oils - Mineral

Eurol Powershift LSA 10W

Mineral "Off-Highway" oil for hydraulic - and transmission systems

Description

Eurol Powershift LSA (Low Sulfated Ash) 10W is a high performance drive line oil, developed for modern demanding "off-road" applications, as well as for trucks requiring a Caterpillar TO-4 or Allison C-4 performance specification.

Eurol Powershift LSA 10W is blended from highly refined mineral base oils and a special for this application developed additive package. Because of these raw materials, the product offers excellent friction characteristics, wear protection and oxidation stability.

Eurol Powershift LSA 10W is recommended for use in powershift and hydrostatic transmissions, manual gearboxes and automatic transmissions, differentials and final drives, hydraulic systems and 'wet brakes' mechanisms.

Applications:

Buses and trucks with Allison manual, power shift and

automatic transmissions.

Off-highway application: earthmoving equipment, agricultural applications and mining industry.

Recommended for use in equipment where Caterpillar TO-4 fluids are prescribed.

The original equipment manufacturer's (OEM) recommendation regarding the selection of the appropriate viscosity grade should always be followed.

Specifications

Approved

ZF TE-ML 03C

ZF registration no.001917

Performance level

Allison C-4

Caterpillar TO-4

Komatsu KES 07.868.1

Physical properties

Density at 20°C	0.862 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	40.1 cSt	ASTM D 445
Viscosity, kinematic at 100°C	6.7 cSt	ASTM D 445
Viscosity Index	123	ASTM D 2270
Viscosity, dynamic (CCS)	3700 cP	ASTM D 2602
Sulphated ash	1.2 wt%	ASTM D 874
Flash point	204 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

E101249

Version 2.1, 17-09-2020

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com