



Quality is in our nature

Tractor oils - Mineral

Eurol Powershift 30 TO-4

Mineral "Off-Highway" oil for hydraulic - and transmission systems

Description

Eurol Powershift 30 TO-4 is a high performance drive line oil, developed for modern demanding "off-road" applications, as well as for trucks requiring a Caterpillar TO-4 or Allison C-4 performance specification. and TO-4 fluids are prescribed.

Eurol Powershift 30 TO-4 is blended from highly refined mineral base oils and a special for this application developed additive package. Because of these raw materials, the product offers excellent friction characteristics, wear protection and oxidation stability.

This oil is recommended for use in power shifts, manual gearboxes and automatic transmissions, final drives, hydraulic systems and 'wet brakes'.

Applications: buses and trucks with Allison manual, power shift and automatic transmissions.

Off-highway application: earthmoving equipment, agricultural applications and mining industry.

Recommended for final drives where Caterpillar TO-2

Specifications

Performance level

Allison C-4

Caterpillar TO-4

Physical properties

Colour	Brown	
Density at 20°C	0.883 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	89.9 cSt	ASTM D 445
Viscosity, kinematic at 100°C	10.7 cSt	ASTM D 445
Viscosity Index	102	ASTM D 2270
Flash point	224 °C	ASTM D 93
Pour point	-21 °C	ASTM D 97

E101265

Version 1.0, 03-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com