



Quality is in our nature

Tractor oils - S.T.O.U.

# Eurol Altrack 15W-40 STOU

## Universal, mineral tractor oil for engine and transmission

### Description

Eurol Altrack 15W-40 STOU is a universal, multi-grade tractor oil (Super Tractor Oil Universal) and is especially developed for application in the engine, transmission and hydraulic system. The product provides a perfect cold start, reduces friction and keeps the engine clean.

Deterging and dispersing additives keep the oil and the system clean from pollution and impurities.

Eurol Altrack 15W-40 STOU can be used all year round in tractors equipped with oil immersed disc brakes (so called 'wet brakes'). Because the oil can be applied in the engine, transmission, hydraulic system and wet brakes, it prevents mistakes in the oil selection and it reduces stock.

Eurol Altrack 15W-40 STOU allows an optimum drain interval for an economic use and maintenance. It provides an uncomplicated exchange of hydraulic equipment.

Eurol Altrack 15W-40 STOU offers a perfect protection against corrosion, oxidation and wear, even under extremely high loads, which occur in transmissions.

### Specifications

<u>Performance level</u>	MIL-L-2104D	MIL-L-2105
API CG-4/SF	Ford WSS-M2C159-B/C	
API GL-4	MIL-L-46152C	
ACEA E3	Ford NH 82009201/2/3	
Allison C-4	Ford WSS-M2C134-D	
MF M1135, MF M1139, MF M1143, MF M1144, MF M1145	John Deere J20C, J27 NH 030 C, NH 024 C, NH 410 B, NH 420 A	
ZF TE ML 06B/06C/06R/07B	Caterpillar TO-2	
Case MS 1206, MS1209	FNHA-2-C201	
MB 227.1	<u>Recommended for use</u>	

### Physical properties

Colour	Brown	
Density at 20°C	0.869 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	104.7 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.7 cSt	ASTM D 445
Viscosity Index	151	ASTM D 2270
Viscosity, dynamic (CCS)	3919 cP	ASTM D 2602
Flash point	198 °C	ASTM D 93
Pour point	-33 °C	ASTM D 97

E105084

Version 2.0, 11-08-2020

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com