



Quality is in our nature

Tractor oils - U.T.T.O.

Eurol Hykrol JD 68

UTTO for agricultural transmissions, clutches, final drives and wet brakes

Description:

Eurol Hykrol JD 68 has been especially developed for transmissions of combined bulldozer, tractor and other agricultural devices, fluid clutches, power steering, hydraulic systems and torque converters.

Eurol Hykrol JD 68 has very favourable friction characteristics and is therefore exceptionally suited for "wet brake"- systems. It prevents so-called 'stick slip'.

Eurol Hykrol JD 68 has a high viscosity index, a very strong oil film and good EP- and anti-wearing properties. It offers good protection against corrosion, oxidation and foam building.

Specifications

<u>Approved</u>	MF M1145
ZF registration no.001971	MF M1143
<u>Performance level</u>	MF M1141
API GL-4	MF M1135
Allison C-4	Volvo WB 101
ZF TE-ML 03E/05F/06K	Ford WSS-M2C134-D
John Deere J20A, J20C	Caterpillar TO-2
Case MS 1206, MS 1207, MS 1210	<u>Recommended for use</u>
CNH MAT 3525	Komatsu KES 07.866
FNHA-2-C-201.00	

Physical properties

Colour	brown	
Density at 20°C	0.871 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	60.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	10.1 cSt	ASTM D 445
Viscosity Index	153	ASTM D 2270
Viscosity, dynamic (CCS)	3250 cP	ASTM D 2602
Flash point	210 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

E105820
Version 3.0, 25-11-2020

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com