



*Quality is in our nature*

Technical fluids - Front fork oils

# Eurol Front Fork Oil SAE 5

## Universal fork oils

### Description

Eurol Front Fork Oil SAE 5 is blended from carefully selected paraffinic base oils with a low pour point and a high viscosity index.

Eurol Front Fork Oil SAE 5 is inhibited with very effective additives, ensuring an exceptional hydraulic springing and shock absorbing action. Scuffing and wear are reduced to a minimum, while a smooth movement is guaranteed. Besides, this oil offers good protection against foam-building and corrosion. Seals are not affected by this product.

Eurol Front Fork Oil SAE 5 has a high thermal and oxidation stability and can be applied in a broad temperature range. Due to the stable viscosity index improvers, the viscosity will stay in grade over a very long time.

### Physical properties

Colour	Red	
Density at 20°C	0.864 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	26.4 cSt	ASTM D 445
Viscosity, kinematic at 100°C	5.2 cSt	ASTM D 445
Viscosity Index	131	ASTM D 2270
Flash point	185 °C	ASTM D 93
Pour point	-51 °C	ASTM D 97

E107980

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com