



Quality is in our nature

# Eurol Transyn 75W-90 GL 4/5

## Synthetic transmission oil for manual gearboxes and final drives

### Description

Eurol Transyn 75W-90 GL4/5 is a synthetic, universal transmission/gear oil which can be applied in both manual gearboxes as well as in final drives, where an API GL-4 or 5 quality oil is prescribed. By this, the product can reduce the stock of transmission/gear oils.

loads, is minimal so that this oil guarantees the right viscosity, even at prolonged drain intervals

Eurol Transyn 75W-90 GL4/5 can be used for the complete drive line. The product contains special additives reducing fuel consumption and eliminating shifting problems. Due to this unique formulation not only wear, but also corrosion and foam building are reduced to a minimum. At high temperatures the oil is protected against thermal oxidation.

Eurol Transyn 75W-90 GL4/5 can be used in synchromesh gearboxes and ensures easy and smooth shifting, even at low temperatures.

Eurol Transyn 75W-90 GL4/5 shows excellent EP (Extreme Pressure) characteristics to cope with heavy loads and vibrations. Viscosity drop, caused by heavy

### Specifications

<u>Performance level</u>	DAF
API GL 4/5	MAN M 3343 Typ M
API MT-1	MAN 342 Type M2
MIL-L-2105 B/C/D	MAN 341 Type Z2
ZF TE-ML	<u>Recommended for use</u>
02B/05A/07A/08A/12E/16B	MB 235.1
/ 16C/16D/17B/19B/21A	MB 235.0
Mack GO-J	Arvin Meritor 076-N
MIL-PRF-2105E	IVECO
Volvo 97310	
Scania STO 1:0	

### Physical properties

Colour	amber	
Density at 20°C	0.883 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	86.7 cSt	ASTM D 445
Viscosity, kinematic at 100°C	15 cSt	ASTM D 445
Viscosity Index	183	ASTM D 2270
Flash point	198 °C	ASTM D 93
Pour point	-42 °C	ASTM D 97

E110075

Version 2.2, 21-07-2021

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com