



Quality is in our nature

Transmission oils - Total drive line

# Eurol Fultrasyn 75W-90 GL4/5

## Fully synthetic oil for manual gearboxes and final drives

### Description

Eurol Fultrasyn 75W-90 is a fully synthetic, universal transmission/gear oil which can be used in both manual gearboxes as well as in final drives and where an API GL 3, 4 or 5 specification is required. By this, the oil offers excellent possibilities for reducing stock.

Pressure) characteristics to cope with high loads and vibrations. Viscosity drop caused by high loads is minimal, so that the right viscosity is guaranteed, even at prolonged drain intervals.

Eurol Fultrasyn 75W-90 is a fully synthetic oil and can be used in the complete drive line. The special additives in this product reduce fuel consumption and eliminate shifting problems.

Eurol Fultrasyn 75W-90 is fully compatible with synchromesh gearboxes and ensures easy shifting, even at very low temperatures.

Because of this unique formulation not only wear, but also corrosion and foam building are reduced to a minimum. At high temperatures, the oil is protected against thermal oxidation.

Eurol Fultrasyn 75W-90 shows excellent EP (Extreme

### Specifications

<u>Performance level</u>	DFS93K219.01	SAE J2360
API GL 4/5	Arvin Meritor 076-N	Scania STO 1:1G
API MT-1	Mack GO-J	
<u>Recommended for use</u>	IVECO	
MAN 342 type M3	MIL-PRF-2105E	
MAN 341 Type E3	Volvo 97312	
MB 235.8	Scania STO 1:0	
ZF TE-ML	Renault (Note Technique	
02B/05B/07A/12B/12/12N/	B0032/2 Annex 3)	
16F/17B/19C/21B	DAF	
DETROIT DIESEL	MAN 341 Type Z2	

### Physical properties

Colour	Yellow	
Density at 20°C	0.87 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	95.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	16.4 cSt	ASTM D 445
Viscosity Index	185	ASTM D 2270
Flash point	211 °C	ASTM D 93
Pour point	-54 °C	ASTM D 97

E110076

Version 3.0, 28-04-2021

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com