



Quality is in our nature

Transmission oils - Fully Synthetic

Eurol Fultrax 75W-140 LS

Fully synthetic "limited-slip" gear oil

Description

Eurol Fultrax 75W-140 LS is a fully synthetic gear oil and has especially been developed for heavy duty transmissions demanding a high viscosity oil, resisting high loads, high pressures and shock loads.

Eurol Fultrax 75W-140 LS is recommended for hypoid transmissions, hub reductions and differentials with or without 'limited slip systems' as used in modern cars.

Eurol Fultrax 75W-140 LS can also be used in many other drive line systems where an API GL-5 gear oil, whether or not with 'limited slip' characteristics, by the OEM is prescribed.

Eurol Fultrax 75W-140 LS has a very high viscosity index, very good low temperature fluidity characteristics and will 'stay-in-grade' even under the most severe working conditions.

Eurol Fultrax 75W-140 LS is based on the most modern additive technology, combined with high quality

synthetic base stocks. Therefore, this lubricant offers a better protection against thermal oxidation and reduces corrosion and wear. Seals are not affected by this product. Special friction reducers make this oil suitable for 'limited slip' applications in both passenger cars as well as in commercial vehicles, tractors and earthmoving equipment. The undesirable noise when taking a turn, is being avoided by using this lubricant.

Specifications

Performance level

- API GL-5
- Ford WSS-M2C192-A
- Scania STO 1:0
- BMW 83 23 9 407 870
- BMW 80 23 2 282 583
- GM/Opel GM 12346140

Recommended for use

- MB 235.61

Physical properties

Colour	Yellow	
Density at 20°C	0.881 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	190 cSt	ASTM D 445
Viscosity, kinematic at 100°C	27.5 cSt	ASTM D 445
Flash point	200 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

E110077

Version 1.2, 22-07-2021

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com