



Quality is in our nature

Transmission oils - Mineral

# Eurol MPG EP 80W90 GL4

Mineral transmission oil for manual gearboxes

## Description

Eurol MPG SAE 80W-90 GL4 is formulated from paraffinic base stocks and additives, including EP (Extreme Pressure) additives according to the phosphor/sulphur technology.

Eurol MPG SAE 80W-90 GL4 is recommended for many types of manual gearboxes and final drives in passenger cars, buses and commercial vehicles and for which an API GL-4 transmission oil is prescribed.

Eurol MPG SAE 80W-90 GL4 also contains additives preventing from corrosion, oxidation and foam building. By this a smooth shifting is guaranteed for a long time. Furthermore, the MPG SAE 80W-90 GL4 has an excellent low temperature fluidity.

Seals are not affected by the Eurol MPG SAE 80W-90 GL4 and the product prevents from undesired deposits.

## Specifications

### Performance level

API GL-4

MIL-L-2105

## Physical properties

Colour	brown	
Density at 20°C	0.883 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	138.4 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.1 cSt	ASTM D 445
Viscosity Index	98	ASTM D 2270
Flash point	232 °C	ASTM D 93
Pour point	-30 °C	ASTM D 97

E110605

Version 1.2, 22-07-2021

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com