



Quality is in our nature

Transmission oils - Mineral

Eurol HPG 80W-90 GL5

Mineral gear oil for hypoid gears and hub reductions

Description

Eurol HPG Gear Oil is a mineral gear oil, formulated according to the latest phosphor - sulphur technology. This special additive technology assures an excellent protection against metal-to-metal contact of the gears under the most severe operating conditions, even under shock loads.

Eurol HPG Gear Oil contains special additives, leaving a protecting oil film for optimum corrosion protection. Furthermore, the SAE 80W and 85W-140 viscosity grades have an excellent low temperature fluidity for an optimum performance during all seasons.

Eurol HPG Gear Oil shows an excellent oxidation and thermal stability. Seals are not affected by this product.

Eurol HPG Gear Oil is recommended for use in hypoid gears, hub reductions, gearboxes, PTO's and differentials where an API GL-5 , MIL-L 2105-D and Mack GO-G are recommended. The SAE 85W-90 viscosity grade can also be applied where MB 235.0 is prescribed.

Specifications

Performance level

API GL-5

MIL-L-2105 B/C/D

Recommended for use

Mack GO-G

Physical properties

Colour	Brown	
Density at 20°C	0.883 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	136.9 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.1 cSt	ASTM D 445
Viscosity Index	100	ASTM D 2270
Flash point	244 °C	ASTM D 93
Pour point	-33 °C	ASTM D 97

E110630

Version 1.3, 18-09-2020

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com