





Gearbox oils - CVT

Eurol CVT 1304

Fully synthetic transmission fluid for CVT's

Description

Eurol CVT 1304 is a fully synthetic transmission oil for the lubrication of modern Continuously Variable Transmissions (CVT's).

Eurol CVT 1304 can be applied in all metal-belt, which are mentioned under Performance Level.

Eurol CVT 1304 offers optimal protection of the CVT under every condition and prevents wear at the metalmetal contact points on the belts and pulleys.

Eurol CVT 1304 protects the metal parts against wear and corrosion as well as inconvenient vibrations. Because of the special additives this oil has a durable quality, even under ongoing pressure.

Eurol CVT 1304 is formulated to prevent air entry and foam building in order to guarantee optimum lubrications.

Specifications

Recommended for use	Dia Queen CVTF J4	Subaru Lineartronic CVTF
BMW 83 22 0 136 376	Elf Matic CVT	Suzuki CVT Green 1
BMW 83 22 0 429 154	EZL-799	Suzuki CVTF Green 2
Chrysler CVTF+4	Ford CVT23	Suzuki NS-2
CVT EZL 799 A	Honda HCF-2	Toyota CVT FE
DAIHATSU AMIX CVT FLUID	Honda HMMF	Toyota CVT TC
DC	MB 236.20	VW G 052 180
Daihatsu CVTF DFE	Mopar CVTF +4	VW G 052 516
Daihatsu/Suzuki TC	Nissan NS-3	Ford WSS-M2C928-A
DEX-CVT	Nissan NS-2	
Dia Queen CVTF J1	Nissan NS-1	

Physical properties

Colour	Amber	
Density at 20°C	0.844 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	33.1 cSt	ASTM D 445
Viscosity, kinematic at 100°C	7 cSt	ASTM D 445
Viscosity Index	184	ASTM D 2270
Flash point	170 °C	ASTM D 93
Pour point	-42 °C	ASTM D 97

E113663 Version 1.1, 18-09-2020