



Quality is in our nature

Coolants & screenwash

## Eurol Antifreeze BS 6580

Meets BS 6580 standard, suitable for open and closed cooling systems

### Description

Eurol Antifreeze is recommended for all cooling systems of combustion engines (both LPG, gasoline and diesel) and other heat transfer systems like central heating installations. It is a homogeneous, stable product, based on mono-ethylene-glycol and formulated according to European car manufacturers instructions.

Vol% in water : 25 30 33 40 50

Frostprotection (°C) : -11 -16 -18 -26 -37

Eurol Antifreeze contains additives, protecting against corrosion and foam-building. Due to the high reserve alkalinity, the cooling system has a long-term protection against corrosion.

Eurol Antifreeze offers the best protection when applied in a concentration of 25 up to 50 vol.%. Concentrations above 65 % should be avoided because of a decreasing frost protection.

Eurol Antifreeze is completely safe for rubbers, plastics, metals, aluminum and alloys. The product is free of nitrites, amines and phosphate.

### Specifications

#### Performance level

BS 6580

ASTM D3306

### Physical properties

Colour	Blue	
Density at 20°C	1.109 kg/l	ASTM D 1298
Flash point	111 °C	ASTM D 93

E503150

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com