

Quality is in our nature



Eurol Diesel System Cleaner

Diesel additive for maintaining the entire fuel system

Description

Eurol Diesel System Cleaner is an additive formulated to remove deposits from combustion chamber, as well as the rest of the fuel system through the use of carefully selected deposit control components.

Eurol Diesel System Cleaner is recommended for use in areas where the diesel quality is such that you experience a significant fuel efficiency reduction, to keep the engine clean and running properly.

Eurol Diesel System Cleaner is also recommended as a preventative measure against corrosion and condensation in the fuel tank.

The 250ml bottle of Eurol Diesel System Cleaner is recommended for use in 35L to 65L of fuel and let the Eurol Diesel System Cleaner run through the fuel system for up to a few hours to ensure a proper cleaning. Add the Eurol Diesel System Cleaner to the fuel tank before refueling.

For best results, use in two consecutive tanks or every 2.500 km. Shorter use intervals can be maintained with city driving and bumper to bumper traffic (stop and go conditions).

Users should consult the Material Safety Data Sheet of Eurol Diesel System Cleaner for information about storage and shelf life. Please ask Eurol Research & Development if any further information is required.

Physical properties

Colour	brown	
Density at 20°C	0.815 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	2.8 cSt	ASTM D 445
Flash point	62 °C	ASTM D 93

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.