



Greases

Quality is in our nature

Eurol Universal Lithium Grease EP 2

Universal lithium grease for various applications

Description

Eurol Universal Lithium Grease EP 2 is a high performance, all-purpose grease with EP additives (without heavy metals) and a good pumpability. It offers an excellent corrosion protection and has very good anti-oxidation properties.

Eurol Universal Lithium Grease EP 2 is extremely suitable for high working temperature conditions, heavy loads, shock loads and where water and dirt may penetrate the greasing point.

Eurol Universal Lithium Grease EP 2 guarantees optimum protection, also under heavy working conditions, extending equipment life-time and reducing maintenance costs.

Eurol Universal Lithium Grease EP 3 is recommended for application in hot/ tropical conditions.

Specifications

Performance level

DIN 51825: KP2.5K-20

ISO-L-XBCHB2.5

Physical properties

Colour	dark brown	
Density at 20°C	0.91 kg/l	ASTM D 1298
NLGI consistency	2-3	
Thickener type	Lithium	
Base Oil Type	Mineral	
Base oil viscosity	290 cSt	ASTM D 445
4-ball weld load	260 kg	ASTM D 2596
Operating temperature	-20 - 130 °C	
Dropping point	185 °C	

E901030

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com