



Quality is in our nature

Greases

# Eurol Molybdenum Disulphide MoS<sub>2</sub>

Multi-Purpose grease with MoS<sub>2</sub> for homokynetic joints

## Description

Eurol Molybdenum Disulphide Grease is a multi-purpose grease, based on mineral base oils, lithium soap thickener and molybdenum disulphide. The latter forms a chemical reaction with metal surfaces which reduces friction (boundary lubrication) to a minimum.

Eurol Molybdenum Disulphide Grease offers good resistance against oxidation and corrosion, and is water-repellent. Furthermore, it has a good mechanical stability, resulting in a very long life-time of the grease.

Eurol Molybdenum Disulphide Grease is recommended for the lubrication of heavily loaded plain bearings, homokynetic joints, chassis lubrication points, earthmoving equipment and agricultural machinery.

## Specifications

### Performance level

DIN 51825: KF2K-30

ISO-L-XCCIB 2

## Physical properties

Colour	Dark grey	
Density at 20°C	0.94 kg/l	ASTM D 1298
NLGI consistency	2	
Thickener type	Lithium	
Base Oil Type	Mineral	
Base oil viscosity	110 cSt	ASTM D 445
4-ball weld load	320 kg	ASTM D 2596
Operating temperature	-30 - 120 °C	
Dropping point	180 °C	

E901070

Version 1.0, 16-02-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com