



Greases

Quality is in our nature

Eurol Marine Grease EP 2/3

For stern tubes and other greasing points on board ships

Description

Eurol Marine Grease is a grease, formulated from high performance refined base oils with a high viscosity. It has been developed for applications where greasing points are exposed to water. This grease surpasses the water repellent properties of calcium thickened greases and has the excellent mechanical stability of a lithium based grease.

Eurol Marine Grease offers a good corrosion protection, excellent EP properties and a good resistance against oxidation. This grease has a good pumpability in grease pumps and will not affect rubber parts. It surpasses traditional calcium based greases with regard to the temperature range.

Of course, Eurol Marine Grease has excellent water repellent properties for both fresh, as well as for salt water. Because of this, it is suitable for all greasing points on board ships and for plain, roller and ball bearings as well.

Specifications

Performance level

DIN 51825: KP2.5K-20

ISO-L-XBCHB2.5

Physical properties

Colour	Brown	
Density at 20°C	0.92 kg/l	ASTM D 1298
NLGI consistency	2-3	
Thickener type	Calcium Lithium	
Base Oil Type	Mineral	
Base oil viscosity	465 cSt	ASTM D 445
4-ball weld load	320 kg	ASTM D 2596
Operating temperature	-20 - 120 °C	
Dropping point	180 °C	

E901160

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com