



Greases

Quality is in our nature

# Eurol PTFE Complex Grease EP 2

Lithium complex with PTFE for a wide application range

## Description

Eurol PTFE Complex Grease EP 2 is based on the well known Eurol Lithium Complex Grease. A percentage PTFE (poly tetra fluor ethylene) is added to this grease, so Eurol PTFE Complex Grease EP 2 offers an even better lubricity.

Eurol PTFE Complex Grease EP 2 is successfully applied in a wide range of applications, operating in a temperature range of -30°C up to +170°C. It is recommended to shorten re-lubrication intervals, if temperatures exceed 200°C.

Eurol PTFE Complex Grease EP 2 is extremely suitable as a 'life-time' lubricant for heavily loaded wheel bearings of trucks, electro motors and kiln bearings. Due to the excellent sealing properties, penetration of dust, dirt and water in the bearing is avoided.

## Specifications

### Performance level

DIN 51825: KPF2N-30

ISO-L-XCDIB2

## Physical properties

Colour	White	
Density at 20°C	0.91 kg/l	ASTM D 1298
NLGI consistency	2	
Thickener type	Lithium Complex	
Base Oil Type	Mineral	
Base oil viscosity	210 cSt	ASTM D 445
4-ball weld load	300 kg	ASTM D 2596
Operating temperature	-30 - 140 °C	
Dropping point	270 °C	

E901280

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com