



Greases

Quality is in our nature

# Eurol BlueStar Grease EP 2

Especially for wheel bearings and wheel hubs of trailers and caravans

## Description

Eurol BlueStar Grease EP 2 has been developed to meet the ongoing technical progress and demands in both the transport sector, as well as in the industrial sector for application in bearings and chassis components.

oxidation stability. Chemical reaction with sealings will not occur.

Eurol BlueStar Grease EP 2 is used in ball, roller, wheel and plain bearings operating under high (shock) loads or vibrations at both high (temporary up to 200 °C.) as well as low temperatures, while keeping its consistency.

Eurol BlueStar Grease EP 2 has an excellent temperature stability and a good adherence capability. In actual practice, it has been proved to be an excellent grease for wheel bearings and hubs of trailers and caravans.

Besides, Eurol BlueStar Grease EP 2 characterizes itself by good corrosion protection properties (also in the presence of water), excellent wear protection and resistance against water wash-out, resulting in a very long life-time. The grease has a good pumpability over a wide temperature range and offers an excellent

## Specifications

### Performance level

DIN KP2N-30

ISO-L-XCDHB 2

NLGI GC-LB

## Physical properties

Colour	Blue	
NLGI consistency	2	
Thickener type	Lithium Complex	
Base Oil Type	Mineral	
Base oil viscosity	220 cSt	ASTM D 445
4-ball weld load	280 kg	ASTM D 2596
Operating temperature	-35 – 150 °C	
Dropping point	260 °C	

E901304

Version 1.3, 22-04-2020

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com